



Data	13,4m³	14m³	14,9m³	15,8m³	16,7m³	18m³	18,5m³	18,9m³	20,3m³	21,2m³	22,5m³	23m³	25,6m³
Body length (mm)	3450	3600	3800	4000	4200	4500	4600	4700	5000	5200	5500	5600	6200
Body width (mm)	2430	2430	2430	2430	2430	2430	2430	2430	2430	2430	2430	2430	2430
Total length (mm)	5613	5763	5963	6163	6363	6663	6763	6863	7163	7363	7663	7763	8363
Height from chassi frame (mm)	2440	2440	2440	2440	2440	2440	2440	2440	2440	2440	2440	2440	2440
Total weight incl oil and chassi brackets (kg)	5080	5100	5140	5180	5220	5460	5480	5500	5560	5600	5660	5680	5810

Technical data

- Work cycle speed: 16-19 Sec
- Packing force: 2,69 Kg/cm²
- Hopper volume: 1,2 m³
- Max hydraulic pressure: 260 Bar
- Flow: 0-140 l/min
- Tank volume: 140 l
- Filter: Return 10 micron
Pressure 10 micron
- Cylinder packer plate: Diam 100/70 mm
- Cylinder carriage plate: Diam 100/50 mm
- Cylinder tailgate: Diam 80/40 mm
- Valve: Load sensing proportional valve
- Pump: Variable
- Electrical system: 24 volt mobile
Can-bus system
- Sides, bottom, roof and other parts that is exposed to wear are made of high tense steel.

- Calculations of volumes are made due to prEN 1501-1